

SPECIFICATION DATA SHEET - FORMED

For the information of Specifiers and Trades

Product Description

Formed is a range of textured glass where one face has been formed over a pattern or mould to create a unique finish to every panel of glass. We recommend that Formed be supplied as a toughened product. Formed is ideal for screening where the transmission of light is still required, combined with the ability to manage the level of visual obscurity.

Colours

Formed is available on all colours of glass including, starphire, clear float, bronze float, grey float and azzurlite.

Sizes

Formed is available at a minimum thickness of 6mm and can be created in 8mm, 10mm, 12mm, 15mm and 19mm thicknesses.

Installation

Formed can be installed into any standard glazing suite that is suitable for the nominated glass thickness. Formed can be grouted into channels using commercially available non shrink grout. Formed can be pin fixed using commercially available fixing systems.

Visual Inspection

No defects should be visible from a distance of three metres or over. Glass must be inspected prior to being installed and Axolotl to be advised immediately of any defects, prior to final installation being performed. *Faiba glass may have organic lines present in the finished panel. These lines are unpredictable & are not a defect, they are a feature of the texture.

Care Instructions

Surfaces should only be cleaned with damp, lint free cloth as part of normal cleaning cycles.
DO NOT USE abrasive or harsh cleaners, scouring pads, steel wool or alkaline cleaners.

Variations to colours

All products provided by Axolotl may vary in colour from panel to panel or batch to batch, due to slight variations in the processed glass used as part of the Formed process. Please also note that lighting within the installed area may also vary the apparent colour, as can the size of a large panel in comparison to a small colour sample.

Toughened Glass

All toughened glass supplied by Axolotl is toughened in accordance with Australian Standards AS/NZS 2208:1996: Safety Glazing Materials in Buildings. Toughened glass can also exhibit some bow or warpage and supplied panels are within Australian Standards. Please see our technical sheet for "toughened glass" for additional information.

Artwork Size Tolerances

Processed glass has a finished tolerance of $\pm 2\text{mm}$, except where templates may be used to provide original sizes. In the case of templates sizes may vary by $\pm 3\text{mm}$ from the original template.

Patterns

All glass that has a pattern may vary slightly in appearance from approved artwork due to the nature of our manufacturing. Variations can include, but not be limited to, layout of the pattern and location of the pattern from panel to panel once a site measure has been completed. Patterns and drawings provided by Axolotl remain the property of Axolotl Group Pty Ltd, and are subject to copy right. Use of these drawings for any other purpose is strictly limited to requests that have been approved in writing by the Axolotl Group Pty Ltd.

Website

Due to the evolving nature of all our products we recommend that up to date information be sourced from the downloadable 'Glass Specification Guide' from our website (www.axolotl.com.au) and we accept no responsibility if outdated technical information has been used.

Maintenance

Clean the glass surface with Windex or other suitable glass cleaners. Never use any thinners, caustics or powder cleansers. Axolotl Formed is suitable for internal and external applications.

Lead Times

Please confirm lead times prior to delivery / commencement of work. The minimum time required for any work carried out in our factory is generally 15-20 working days, however this may increase for large or intricate surfaces.

NOTE FOR SPECIFIERS -

PLEASE ENSURE SPECIFICATION SHEET IS COPIED & ATTACHED TO TENDER DRAWINGS FOR THE REFERENCE OF ALL RELEVANT TRADES.

For further information, technical assistance or costing please contact:

Company	Axolotl Group Pty Ltd
Address	6 / 73 Beauchamp Road, Matrville, N.S.W, 2036.
Phone	02 9666 1207
Email	kris@axolotl.com.au
Website	www.axolotl.com.au